

5000S

Features & Specs

DESCRIPTION

The 5000S touch screen will replace the 3001, 4000 and 4000 MKII control systems. The 5000S represents a major advancement in control technology, offering durability and reliability. Most importantly, it is designed to incorporate the old, current and future control technology with all the functionality of Zero Speed™, underway and retractable requirements.

FEATURES:

PLATFORM: The 5000S uses a plug-in/add-on modular platform with an expandable capacity, designed to accommodate all systems with cost effective solutions for the more basic systems.

INTERFACE: The 5000S interface is via a standard hi def 10" touch screen, with an optional glass bridge systems (GBI) interface and can support multiple touch screens with full system control and monitoring capabilities.

OPTIONAL CAPABILITIES: With an internet access module, the 5000S makes remote access to Quantum a major advantage. Through a dedicated, secure server, Quantum is able to assist with troubleshooting and operational questions. Additionally, data can be recorded and downloaded later, when bandwidth is limited.

| Electrical Control Box | | Touch Screen | |
|------------------------|------------------------------|----------------------|-----------------------|
| Dimensions | 600x760x210 or 500x600x210mm | Dimensions | 282x197x56mm |
| Weight | 47Kg large, 25Kg smaller | Operation Voltage | 24VDC |
| IP Rating | 54 | Power Draw | 24W |
| Operating Temp | -20°C to +60°C | Interface Connection | Ethernet |
| Voltage | 24VDC | Operating Temp | -20°C to +60°C |
| Power Draw | 700W (max) | Construction Type | Aluminum/Glass/Steel |
| Roll Sensor | | Resolution | 1280x800 |
| Dimensions | 231x127x60 | Luminance | 800 cd/m ² |
| Weight | 1Kg | | |
| IP Rating | 65 | | |
| Operation Temp | -5°C to +60°C | | |

Equipment is covered by Quantum's 1-year comprehensive warranty. Service and technical support are available worldwide.